



Gammacolor s.r.l.
Via Zeuner,5 20822 Seveso (MB) Italy
tel. +39 0362550550 fax +39 0362551915
email info@gammacolorsrl.com

Sistema di gestione qualità
certificato secondo la UNI EN ISO
9001:2015 da Certiquality.

p.IVA 00736390964
Cod.Fisc. 02639210158
c.c.i.a. Milano n. 927455
Codice APP/ISS azienda 00736390964



Associazione Tessile e Salute
Azienda associata

GAMMAPRET AMR

Self-crosslinking acrylic resin

FEATURES

Appearance: White liquid

Chemical nature: Acrylic copolymer in water dispersion

pH: 2 - 4

Ionic character: Anionic, non-ionogenic

Solubility: Miscible in water in all proportions

Chemical stability: Stable with the usual finishing auxiliaries

Compatibility: With anionic and non-ionic derivatives

Stability and storage: Protect from frost. The product must be stored in the original sealed packaging at temperature between 5 and 40 ° C

PROPERTY

GAMMAPRET AMR is a Self-crosslinking acrylic resin, non-yellowing, usable with normal finishing products; it gives a full, rigid hand, and in the case of knitting fabric it acts as an anti-roll.

APPLICATION

GAMMAPRET AMR is specific for textile finishing. It can be used alone or in mixture with other products such as glyoxal, vinyl and polyurethane resins.

It is also employed as an anti-rolling agent for selvages and for the finishing of cotton garments.

DOSAGE

From 5 to 30 g / l GAMMAPRET AMR according to the desired effect.

The above data are the result of accurate studies and/or of the experience acquired; however, they are to be taken as an indication and in any case with no guarantee on our side as far as employment is concerned. The data contained in this data sheet are not to be regarded as technical specifications. For information, please contact: **e-mail address**

info@gammacolorsrl.com