



Gammacolor s.r.l.
Via Zeuner, 5 20822 Seveso (MB) Italy
tel. +39 0362550550 fax +39 0362551915
email info@gammacolorsrl.com



Associazione Tessile e Salute
Azienda associata

p.IVA 00736390964 C.F. 02639210158 c.c.i.a. Milano n. 927455 Codice ISS azienda 00736390964

ANTIBASTONANTE GAMMA

Features: it gives a slipping and anti crack mark effect for cotton dyeing..

Chemical composition: emulsified fat compound, weakly anionic nature.

Solubility: freely soluble or emulsifiable in cold or hot water

Appearance: clear yellow liquid

pH sol. 1:10: 6-8

Stability: good resistance to normal concentrations of use with alkalis, acids and electrolytes.

Properties: The product is suitable to improve the slipping of the material to be dyed during the finishing process. On a substrate particularly delicate gives excellent slippery properties avoiding the dreaded markings of the folds. The apparatus for dyeing may also be more loaded to reduce the bath ratio, with a consequent saving of the auxiliary and energy. The product does not in any way affect intensity or color tone.

Application: ANTIBASTONANTE GAMMA can be used, thanks to its low foaming behavior, on all equipment for dyeing and finishing. For its resistance to acids it is also used in a single- bath dyeing of blends with reactive dyes, acid and / or dispersion dyes. It is recommended to add the ANTIBASTONANTE GAMMA at the beginning of the dyeing, before dyes and the auxiliaries, so that in a short time the material completely absorbs the product.

Typical use: 2% - max. 7%

Do not exceed the recommended doses, because it can delay slightly the exhaustion of the dye.

Keywords: anti crack mark, slipping

These notes are for information purposes only and does not imply any liability on the part the Gammacolor. It is the responsibility of the customer to verify the suitability of the product to its special processing. For information: e-mail: info@gammacolorsrl.com